

CCNA 1: Network Fundamentals Final Set C

1. A PC can not connect to any remote websites, ping its default gateway, or ping a printer that is functioning properly on the local network segment. Which action will verify that the TCP/IP stack is functioning correctly on this PC?

Use the ipconfig /all command at the host's command prompt.

****Use the ping 127.0.0.1 command at the command prompt.**

Use the traceroute command at the command prompt to identify any failures on the path to the gateway.

Use FTP to check for connectivity to remote sites.

Download a troubleshooting tool from the PC manufacturer's website.

2. Refer to the exhibit. Which set of devices contains only intermediary devices?

****A, B, D, G**

A, B, E, F

C, D, G, I

G, H, I, J

3. Refer to the exhibit. When computer A sends a frame to computer D, what computers receive the frame?

****only computer D**

only computer A and computer D

only computer B, computer C, and computer D

all computers

4. Which password is automatically encrypted when it is created?

vtty

aux

console

****enable secret**

enable password

5. Which three statements characterize the transport layer protocols? (Choose three.)

****TCP and UDP port numbers are used by application layer protocols.**

TCP uses port numbers to provide reliable transportation of IP packets.

UDP uses windowing and acknowledgments for reliable transfer of data.

****TCP uses windowing and sequencing to provide reliable transfer of data.**

****TCP is a connection-oriented protocol. UDP is a connectionless protocol.**

6. Which type of media is immune to EMI and RFI? (Choose two.)

10 Base-T

10 Base-2

10 Base-5

****100 Base-FX**

100 Base TX

****1000 Base LX**

7. Refer to the exhibit. A technician is working on a network problem that requires verification of the router LAN interface. What address should be pinged from this host to confirm that the router interface is operational?

127.0.0.1

192.168.64.196

**192.168.254.1

192.168.254.9

192.168.254.254

8. Refer to the exhibit. The diagram represents the process of sending email between clients.

Select the list below that correctly identifies the component or protocol used at each numbered stage of the diagram.

1.MUA 2.MDA 3.MTA 4.SMTP 5.MTA 6.POP 7.MDA 8.MUA

1.MUA 2.POP 3.MDA 4.SMTP 5.MTA 6.MDA 7.SMTP 8.MUA

1.MUA 2.POP 3.SMTP 4.MDA 5.MTA 6.SMTP 7.POP 8.MUA

1.MDA 2.SMTP 3.MTA 4.SMTP 5.MTA 6.MUA 7.POP 8.MDA

**1.MUA 2.SMTP 3.MTA 4.SMTP 5.MTA 6.MDA 7.POP 8.MUA

9. Refer to the exhibit. What function does router RT_A need to provide to allow Internet access for hosts in this network?

**address translation

DHCP services

ftpd

web server

10. Refer to the exhibit. The network containing router B is experiencing problems. A network associate has isolated the issue in this network to router B? What action can be performed to correct the network issue?

issue the ip address command on interface FastEthernet 0/0

**issue the no shutdown command on interface FastEthernet 0/1

issue the clock rate command on interface Serial 0/0/0

issue the description command on interface Serial 0/0/1

11. Which three IPv4 addresses represent a broadcast for a subnet? (Choose three.)

**172.16.4.63 /26

172.16.4.129 /26

**172.16.4.191 /26

172.16.4.51 /27

**172.16.4.95 /27

172.16.4.221 /27

12. What are three characteristics of CSMA/CD? (Choose three.)

Devices can be configured with a higher transmission priority.

A jam signal indicates that the collision has cleared and the media is not busy.

**A device listens and waits until the media is not busy before transmitting.

The device with the electronic token is the only one that can transmit after a collision.

**All of the devices on a segment see data that passes on the network medium.

**After detecting a collision, hosts can attempt to resume transmission after a random time delay has expired.

13. In a Cisco IOS device, where is the startup-configuration file stored?

Flash

**NVRAM

RAM

ROM

14. A routing issue has occurred in your internetwork. Which of the following type of devices should be examined to isolate this error?

access point

host

hub

**router

switch

15. Which OSI layer protocol does IP rely on to determine whether packets have been lost and to request retransmission?

application

presentation

session

**transport

16. Due to a security violation, the router passwords must be changed. What information can be learned from the following configuration entries? (Choose two.)

```
Router(config)# line vty 0 3
```

```
Router(config-line)# password c13c0
```

```
Router(config-line)# login
```

The entries specify three Telnet lines for remote access.

**The entries specify four Telnet lines for remote access.

The entries set the console and Telnet password to "c13c0".

Telnet access will be denied because the Telnet configuration is incomplete.

**Access will be permitted for Telnet using "c13c0" as the password.

17. Which prompt represents the appropriate mode used for the copy running-config startup-config command ?

Switch-6J>

**Switch-6J#

Switch-6J(config)#

Switch-6J(config-if)#

Switch-6J(config-line)#

18. Which combination of network id and subnet mask correctly identifies all IP addresses from 172.16.128.0 through 172.16.159.255?

172.16.128.0 255.255.255.224

172.16.128.0 255.255.0.0

172.16.128.0 255.255.192.0

**172.16.128.0 255.255.224.0

172.16.128.0 255.255.255.192

19. When must a router serial interface be configured with the clock rate command?

when the interface is functioning as a DTE device

when the interface timers have been cleared

when the connected DTE device is shut down

**when the interface is functioning as a DCE device

20. When connectionless protocols are implemented at the lower layers of the OSI model, what are usually used to acknowledge the data receipt and request the retransmission of missing data?

connectionless acknowledgements

**upper-layer connection-oriented protocols

Network layer IP protocols

Transport layer UDP protocols

21. A technician is asked to secure the privileged EXEC mode of a switch by requiring a password. Which type of password would require this login and be considered the most secure?

console

enable

**enable secret

VTY

22. Refer to the exhibit. What is required on host A for a network technician to create the initial configuration on RouterA?

a FTP client

a telnet client

**a terminal emulation program

a web browser

23. Refer to the exhibit. A network administrator remotely accesses the CLI of RouterB from PC1. Which two statements are true about the application layer protocol that is used to make this connection? (Choose two.)

The data is encrypted.

**The connection type is called a VTY session.

A server process is running on PC1.

A GET request is sent to RouterB.

**The application name is the same for the service, protocol, and client.

24. The Layer 4 header contains which type of information to aid in the delivery of data?

**service port number

host logical address

device physical address

virtual connection identifier

25. Refer to the exhibit. What two facts can be determined about the exhibited topology? (Choose two.)

**A single broadcast domain is present

Two logical address ranges are required.

Three broadcast domains are shown.

Four networks are needed.

**Five collision domains exist.

26. Refer to the exhibit. A network technician is trying to determine the correct IP address configuration for Host A. What is a valid configuration for Host A?

IP address: 192.168.100.19; Subnet Mask: 255.255.255.248; Default Gateway:

192.16.1.2

**IP address: 192.168.100.20; Subnet Mask: 255.255.255.240; Default Gateway:

192.168.100.17

IP address: 192.168.100.21; Subnet Mask: 255.255.255.248; Default Gateway:

192.168.100.18

IP address: 192.168.100.22; Subnet Mask: 255.255.255.240; Default Gateway: 10.1.1.5

IP address: 192.168.100.30; Subnet Mask: 255.255.255.240; Default Gateway:

192.168.1.1

IP address: 192.168.100.31; Subnet Mask: 255.255.255.240; Default Gateway:

192.168.100.18

27. Refer to the exhibit. Cable 1 and cable 2 have the ends wired for specific physical layer requirements. The table lists each segment by number and the cable which has been installed by the network technician between the network components on that segment.

From the data

given, which segments have the correct cable installed? (Choose three.)

**segment1

segment2

**segment3

**segment4

segment5

28. What is true regarding network layer addressing? (Choose three.)

uses a flat structure

prevent broadcasts

**heirarchical

**uniquely identifies each host

48 bits in length

**contains a network portion

29. Refer to the exhibit. A router, whose table is shown, receives a packet that is destined for 192.168.1.4. How will router treat the packet?

The packet will be dropped.

The packet will be forwarded via FastEthernet 0/0.

**The packet will be forwarded to the destination host.

The packet will be forwarded to the 192.168.1.3 next-hop address.

30. Refer to the exhibit. Which two statements describe the information that is represented in the header? (Choose two.)

This is a server response.

The UDP protocol is being used.

**The destination port indicates a Telnet session.

**The return segment will contain a source port of 23.

The next session originated from the client of this session will use the source port number 13358.

31. Refer to the exhibit. What is the correct destination socket number for a web page request from Host A to the web server?

00-08-a3-b6-ce-46

**198.133.219.25:80

<http://www.cisco.com>

C 198.133.219.0/24 is directly connected, FastEthernet0/0

32. During the encapsulation process, which identifiers are added at the transport layer?

two networks routing the packets

**two applications communicating the data

two hosts at either end of the communication

two nodes on the local network exchanging the frame

33. Refer to the exhibit. A student has wired each end of a CAT 5e cable as shown. What is the result? (Choose two.)

The cable is unusable and must be rewired.

The cable is suitable for use as a Gigabit Ethernet straight-through.

**The cable is suitable for use as a Fast Ethernet crossover.

The cable is suitable for use as a rollover cable.

The cable is suitable for use as a Gigabit Ethernet crossover.

**The cable is suitable for use between two 100 Mbps Auto-MDIX capable switches.

34. Refer to the exhibit. Assume all devices are using default configurations. How many subnets are required to address the topology that is shown?

- 1
- **3
- 4
- 5
- 7

35. Refer to the exhibit. On the basis of the IP configuration that is shown, what is the reason that Host A and Host B are unable to communicate outside the local network?

- Host A was assigned a network address.
- Host B was assigned a multicast address.
- Host A and Host B belong to different networks.
- **The gateway address was assigned a broadcast address.

36. Refer to the exhibit. Each media link is labeled. What type of cable should be used to connect the different devices?

- Connection 1 - rollover cable
- Connection 2 - straight-through cable
- Connection 3 - crossover cable
- Connection 1 - crossover cable
- Connection 2 - rollover cable
- Connection 3 - crossover cable
- Connection 1 - straight-through cable
- Connection 2 - crossover cable
- Connection 3 - crossover cable
- **Connection 1 - straight-through cable
- **Connection 2 - crossover cable
- **Connection 3 - straight-through cable
- Connection 1 - crossover cable
- Connection 2 - straight-through cable
- Connection 3 - crossover cable

37. Refer to the exhibit. What does the IP address 192.168.33.2 represent?

- The host's default gateway.
- The host's IP address.
- **The host's primary domain name server.
- The IP address of the website resolver1.mooki.local.
- The IP address of the host's homepage.

38. Refer to the exhibit. What two facts can be determined from the information that is given? (Choose two.)

- This exchange is part of the three-way handshake.
- The source port indicates that a Telnet session has been initiated.

The data is flowing from server to client.

**The destination port indicates that an HTTP session has been initiated.

**The data listed is associated with the transport layer.

The source port does not support communication with the destination port that is listed.

39. Which of the following are the address ranges of the private IP addresses? (Choose three.)

**10.0.0.0 to 10.255.255.255

200.100.50.0 to 200.100.25.255

150.150.0.0 to 150.150.255.255

**172.16.0.0 to 172.31.255.255

**192.168.0.0 to 192.168.255.255

127.16.0.0 to 127.31.255.255

40. Which two functions of the OSI model occur at layer two? (Choose two.)

**physical addressing

encoding

routing

cabling

**media access control

41. Which range of port numbers are reserved for services that are commonly used by applications that run on servers?

0 to 255

**0 to 1023

1024 to 49151

49152 to 65535

42. As network administrator, what is the subnet mask that allows 510 hosts given the IP address 172.30.0.0?

255.255.0.0

255.255.248.0

255.255.252.0

**255.255.254.0

255.255.255.0

255.255.255.128

43. Refer to the exhibit. The tracert command is initiated from PC1 to the destination PC4. Which device will send a response to the initial packet from PC1?

**London

Paris

Athens

Ankara

PC4

44. Refer to the exhibit. Host A is transmitting data to host B. What addresses will host A

use to for the destination IP and MAC addresses in this communication?

Destination MAC: BBBB:BBBB:BBBB Destination IP: 172.22.0.62

Destination MAC: DDDD:DDDD:DDDD Destination IP: 172.22.0.75

Destination MAC: EEEE:EEEE:EEEE Destination IP: 172.22.0.62

Destination MAC: BBBB:BBBB:BBBB Destination IP: 172.22.0.75

**Destination MAC: EEEE:EEEE:EEEE Destination IP: 172.22.0.75

Destination MAC: DDDD:DDDD:DDDD Destination IP: 172.22.0.94

45. Refer to the exhibit. Which logical topology best describes the exhibited network?

star

ring

point-to-point

**multiaccess

mesh

46. Examine the graphic with current configurations. Host A in the Clerical offices failed and was replaced. Although a ping to 127.0.0.1 was successful, the replacement computer can not access the company network. What is the likely cause of the problem?

IP address incorrectly entered

network cables unplugged

**subnet mask incorrectly entered

network card failure

47. Refer to the exhibit. With the router running NAT, what IP addresses can be applied to the computer to allow access to the Internet? (Choose three.)

192.168.18.38

192.168.18.48

**192.168.18.49

**192.168.18.52

**192.168.18.59

192.168.18.63

48. Refer to the exhibit. What three statements are true about the IP configuration that is shown? (Choose three.)

**The address that is assigned to the computer represents private addressing.

**The computer is unable to communicate outside of the local network.

The network of this computer can have 126 hosts.

**The prefix of the computer address is /27.

The IP address that is assigned to the computer is routable on the Internet.

The IP address that is assigned to the computer is a broadcast address.

49. Refer to the exhibit. Host A attempts to establish a TCP/IP session with host C. During this attempt, a frame was captured with the source MAC address 0050.7320.D632 and the destination MAC address 0030.8517.44C4. The packet inside the captured frame has an IP source address 192.168.7.5, and the destination IP address is 192.168.219.24. At which point in the network was this packet captured?

- leaving host A
- leaving ATL
- **leaving Dallas**
- leaving NYC

50. Which of the following OSI layers offers reliable, connection-oriented data communication services?

- application
- presentation
- session
- **transport**
- network